



iPOLISHER L Series Units



iPOLISHER units are a simple, practical and inexpensive high purity storage and distribution systems designed for stand alone service or integration for use with any iPURE pure water generation system.

Each assembly efficiently combines several pure water treatment processes into a single, compact unit designed to maintain and distribute pure water. These units can store and distribute from 5 to 90 gallons per minute of high purity water and when configured appropriately can deliver water meeting any of the current pharmaceutical, industrial and/or laboratory reference standards.

Each system is supplied completely assembled, factory tested and ready for field installation. Typical applications for these systems include; ultra-pure water for the electronics, pharmaceutical and power industries; process water for the food, beverage and chemical industries and pure water for research, pilot facilities and laboratories.



iPOLISHER - L Series

Specifications

Model	L-005	L-010	L-020	L-030	L-050	L-090
Design						
Distribution Flow Rate GPM (LPM)*	5.0 (18.9)	10.0 (37.9)	20.0 (75.7)	30.0 (113.6)	40.0-50.0 (151.4-189.3)	60.0-90.0 (227.1-340.7)
Draw Flow Rate GPM (LPM)	2.0 (7.8)	6.0 (22.7)	14.0 (53.0)	24.0 (90.8)	30.0-40.0 (113.6-151.4)	45.0-75.0 (170.3-283.9)
Supply Pressure PSIG (BAR)*	125.0 (8.6)	125.0 (8.6)	125.0 (8.6)	125.0 (8.6)	125.0 (8.6)	125.0 (8.6)
Max Temp °F (°C)	95.0 (35.0)	95.0 (35.0)	95.0 (35.0)	95.0 (35.0)	95.0 (35.0)	95.0 (35.0)
Connections						
Suction	1" Tri-Clamp	1" Tri-Clamp	1 1/2" Tri-Clamp	1 1/2" Tri-Clamp	2" Tri-Clamp	2 1/2" Tri-Clamp
Discharge	1" Tri-Clamp	1" Tri-Clamp	1 1/2" Tri-Clamp	1 1/2" Tri-Clamp	2" Tri-Clamp	2 1/2" Tri-Clamp
Drain	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Pumps						
Pump Type	Centrifugal Multi-Stage	Centrifugal Multi-Stage	Centrifugal Multi-Stage	Centrifugal Multi-Stage	Centrifugal Multi-Stage	Centrifugal Multi-Stage
Motor HP (KW)	3.0 (2.2)	3.0 (2.2)	3.0 (2.2)	5.0 (3.7)	7.5 (5.5)	15.0 (11.0)
RPM @ 60/50 HZ****	3450 (2900)	3450 (2900)	3450 (2900)	3450 (2900)	3450 (2900)	3450 (2900)
UV Sterilization						
Type	254 nm	254 nm	254 nm	254 nm	254 nm	254 nm
Final Filter						
Style	Single	Single	Single	Multi-Round	Multi-Round	Multi-Round
Rating	0.2 Micron	0.2 Micron	0.2 Micron	0.2 Micron	0.2 Micron	0.2 Micron
Quantity	1	1	1	4	4	4
Length	20"	20"	20"	10"	20"	30"
Electrical						
Standard Voltage	460V/60 HZ/3 PH	460V/60 HZ/3 PH	460V/60 HZ/3 PH	460V/60 HZ/3 PH	460V/60 HZ/3 PH	460V/60 HZ/3 PH
Optional Voltage	230V/60 HZ/3 PH	230V/60 HZ/3 PH	230V/60 HZ/3 PH	230V/60 HZ/3 PH	230V/60 HZ/3 PH	230V/60 HZ/3 PH
System Dimensions**						
L x W x H inch (cm)	37 x 48 x 67 (94 x 121 x 170)	37 x 48 x 67 (94 x 121 x 170)	37 x 48 x 67 (94 x 121 x 170)	57 x 57 x 60 (145 x 145 x 152)	57 x 57 x 60 (145 x 145 x 152)	58 x 71 x 60 (147 x 180 x 152)
Weight lb. (Kg)	1500 (680)	1500 (680)	1500 (680)	2000 (907)	2000 (907)	2500 (1134)

* Product flow rates and recovery are based on equipment test parameters

** Does not include operating space requirements

**** Operation at 50 HZ supply will reduce unit pressures and flow rates. Consult factory for details.

Operating Limits

Maximum Feed Temperature °F (°C)	95 (35.00)	Maximum Free Chlorine ppm	0
Minimum Feed Temperature °F (°C)	40 (4.44)	Maximum pH (Continuous)	11
Maximum Ambient Temperature °F (°C)	120 (48.89)	Minimum pH (Continuous)	5
Minimum Ambient Temperature °F (°C)	40 (4.44)	Maximum pH (Cleaning 30 Min.)	12
Minimum Suction Pressure ft (m)	4 ft (1.2)	Minimum pH (Cleaning 30 Min.)	2
Maximum Operating Pressure psi (bar)	125 (8.6)	Maximum Turbidity NTU	<1

L Series Units

Standard Features

- Standard flow ranges from 5 to 90 GPM
- Modular design for easy expansion
- Epoxy-coated steel frame for floor mounting
- Stainless steel, high efficiency, multiple stage supply pump
- UV sterilization system
- Sub-micron absolute filtration system
- High purity shut off valves
- Stainless steel pressure gauges
- Sanitary tri-clamp connections

Optional Features

- Duplex Pump System
- Duplex final filtration system
- Water quality monitoring system
- Flow or pressure monitoring system
- Ozone generation and distribution system
- Pure water cooling system
- Pure water divert system
- Cartridge ultra-filtration system
- PP or PVDF pipe manifolds